

Tehničke karakteristike proizvoda Karakteristike

13975 mini Mureva - za modularni uređaj - 1 otvor - 3 modula



Osnovne informacije

Grupa proizvoda	Mureva
Ime proizvoda	Mureva Enclosure
Tip proizvoda ili komponente	Orman
Tip ormara	Mini orman za modularne uređaje
Opis montažne ploče	Sa izrezima

Dopunske informacije

Montaža ormara	Površinska
Broj 18 mm modula po redu	3
Ukupan broj 18 mm modula	3
Broj horizontalnih redova	1
Električna klasa izolacije	Dupla izolacija Klasa II
Obezbeđena oprema	1 set oznaka
Tip prednjeg poklopca	Providni
[in] nazivna struja	63 A
Tip šine	DIN
Broj otvora pg iso	1
Opis opcija zaključavanja	Opciona bravica
Materijal kućišta	Samogasivi polimer
Širina	80 mm
Visina	150 mm
Dubina	98 mm
Unutrašnja dubina	56 mm
Boja	Vrata: prozirnozelena Orman: svetlosiva (RAL 7035)

Okruženje

Standardi	IEC 61439-3 IEC 60670 IEC 60695-2-1 EN 50262
Otpornost na vatru	650 °C u skladu sa IEC 60695-2-1
Ip stepen zaštite	IP65 u skladu sa IEC 60529
Ik stepen zaštite	IK09 u skladu sa EN 50102
Environmental characteristics (UV)	UV otpornost: klasa 3 u skladu sa ISO 4582:2010 Test ultraljubičaste degradacije u skladu sa ISO 4892-2:2013
Kategorija prenapona	II
Temperatura okoline za rad uređaja	-25...60 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8,000 cm
Package 1 Width	15,000 cm
Package 1 Length	10,000 cm
Package 1 Weight	255,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	22,500 cm
Package 2 Width	34,500 cm
Package 2 Length	40,000 cm
Package 2 Weight	5,412 kg
Unit Type of Package 3	P12
Number of Units in Package 3	480
Package 3 Height	80,000 cm
Package 3 Width	80,000 cm
Package 3 Length	120,000 cm
Package 3 Weight	142,200 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	Da
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Nema potrebe za namenskim operacijama recikliranja
Učinak u vezi sa sadržajem halogena	Proizvod bez halogena
Minimum percentage of recycled plastic content	24

Ugovorna garancija

Garancija	18 meseci
-----------	-----------