

Tehničke karakteristike proizvoda

Karakteristike

47887

Indication contacts, MasterPact NW08 to NW63, additional block, 4 ON/OFF contacts



Osnovne informacije

Tip proizvoda ili komponente	Pomoćni kontakt
Kratko ime uređaja	4 OF
Kompatibilnost grupe proizvoda	Masterpact Masterpact NW Easypact EasyPact MVS Easypact EasyPact EXE
Sastav signalnih kontakata	4 NO/NC

Dopunske informacije

Tip pomoćnog kontakta	Standardni Za niže vrednosti napona
Breaking capacity (A)	AC-12: 10 A at 240/380 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 10 A at 480 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 6 A at 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 DC-12: 10 A at 24/48 V DC conforming to EN/IEC 60947-2 DC-12: 10 A at 125 V DC conforming to EN/IEC 60947-2 DC-12: 3 A at 250 V DC 50/60 Hz conforming to EN/IEC 60947-2 8 A at 480 V AC 50/60 Hz conforming to UL 489 AC-12: 6 A at 600 V AC 50/60 Hz conforming to UL 489 6 A at 250 V DC conforming to UL 489
Minimalno opterećenje	100 MA pri 24 V 2 mA pri 15 V

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,1 cm
Package 1 Width	4,6 cm
Package 1 Length	6,8 cm
Package 1 Weight	87 g

Održivost ponude

Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu

Operacije i opisi

Operation	600
Duration of operation	4 minuta
Opis operacije	Montaža i testiranje

Ugovorna garancija

Garancija	18 months
-----------	-----------