

Tehničke karakteristike proizvoda

Karakteristike

48478

EF combined connected/closed contact,
MasterPact NW drawout, 1 changeover
contact, low level 3A/240VAC, spare part



Osnovne informacije

Kratko ime uređaja	EF kontakt
Tip proizvoda ili komponente	Pomoćni kontakt
Primena uređaja	Upravljanje
Kompatibilnost grupe proizvoda	Masterpact Masterpact NW
Signalni kontakt	1 NO/NC

Dopunske informacije

Tip pomoćnog kontakta	Za niže vrednosti napona
Operacije pomoćnih kontakata	Položaj spojen
Način montiranja	Izvlačivo
[ie] nazivna struja	DC-12: 0,3 A pri 250 V DC DC-12: 0,8 A pri 125 V DC DC-12: 2,5 A pri 24/48 V DC AC-12: 5 A pri 240 V AC 50/60 Hz AC-12: 5 A pri 380 V AC 50/60 Hz AC-12: 5 A pri 240/380 V AC 50/60 Hz
Minimalno opterećenje	2 mA pri 15 V

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,0 cm
Package 1 Width	15,0 cm
Package 1 Length	10,0 cm
Package 1 Weight	34,0 g
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	30,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm
Package 2 Weight	3,887 kg

Održivost ponude

Propis REACH	 REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	У складу са изузецима
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da

Ugovorna garancija

Garancija	18 months
-----------	-----------