

Tehničke karakteristike proizvoda

Karakteristike

54443

Spoljni napojni modul 110 V AC



Osnovne informacije

Tip proizvoda ili komponente	Spoljašnji modul napajanja
Primena uređaja	Napajanje
Kompatibilnost grupe proizvoda	Masterpact Masterpact NT prekidač Masterpact Masterpact NW prekidač Compact Compact NS prekidač Compact Compact NSX prekidač Compact Compact NSX DC prekidač PowerPact PowerPact Multistandard prekidač Masterpact Masterpact MTZ1 prekidač Masterpact Masterpact MTZ2 prekidač Masterpact Masterpact MTZ3 prekidač PowerPact PowerPact H prekidač PowerPact PowerPact J prekidač PowerPact PowerPact L prekidač
Pribor / posebni tip	Pribor upravljačke jedinice

Dopunske informacije

Ime zaštitne jedinice	Micrologic
[us] nazivni napon	110...130 V AC 50/60 Hz tolerancija: +10 % -15 %
Napon izlaza	24 V DC +/-5 %
Kategorija prenapona	IV u skladu sa IEC 62477-1
Visina	88 mm
Širina	105 mm
Dubina	59 mm

Okruženje

Kompatibilnost	Eksterno napajanje
----------------	--------------------

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7,0 cm
Package 1 Width	9,7 cm
Package 1 Length	12,3 cm
Package 1 Weight	349,0 g
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Height	30,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm
Package 2 Weight	13,051 kg

Održivost ponude

EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da