

Tehničke karakteristike proizvoda

Karakteristike

A9A26907

Pomoćni kontakt, Acti9 A9A, iSD, 1 C/O,
100mA-6A, 24VAC-415VAC, 24VDC-130VDC,
donji priključak



Osnovne informacije

Range of product	Acti 9
Tip proizvoda ili komponente	Kontakt greške
Kratko ime uređaja	iSD
Signalni kontakt	1 C/O
[in] nazivna struja	0,1...6 A at 24...240 V, AC 50/60 Hz 0,1...3 A at 415 V, AC 50/60 Hz 0,1...6 A at 24 V, DC 0,1...2 A at 48 V, DC 0,1...1,5 A at 60 V, DC 0,1...1 A at 130 V, DC
9 mm redovi	1

Dopunske informacije

[ui] nazivni napon izolacije	500 V
[uimp] nazivni podnosivi impulsni napon	4 kV
Lokalna signalizacija	Mehanički indikator
Način montiranja	Sistemom na klik
Lokacija za montiranje	Left side of circuit-breaker
Nosači za montažu	DIN šina
Razvodni blok češljaste sabirnice	Gornji: DA
Visina	86 mm
Širina	9 mm
Dubina	73 mm
Masa proizvoda	33 g
Boja	Bela
Povezivanje - priključci	Vijčani priključni blok (donji) 1 kabl(ovi) 0,5...2,5 mm ² - fleksibilni Vijčani priključni blok (donji) 1 kabl(ovi) 1...4 mm ² - kruti Vijčani priključni blok (donji) 2 kabl(ovi) 2,5 mm ² - kruti Vijčani priključni blok (donji) 2 kabl(ovi) 1,5 mm ² - fleksibilni sa kablovskim završetkom
Dužina ogoljenog dela žice	10 mm
Moment pritezanja	1 N.m donji

Okruženje

Standardi	EN/IEC 60947-5-1 GB/T 14048.5
Sertifikacija proizvoda	CE[RETURN]UKCA
Oznake kvaliteta	EAC CCC CMIM
Ip stepen zaštite	IP20
Stepen zaprljanosti	3
Tropikalizacija	2
Relativna vlažnost	95 % pri 55 °C

Temperatura okoline za rad uređaja	-35...70 °C
Temperatura okoline za skladištenje	-40...85 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2,100 cm
Package 1 Width	8,000 cm
Package 1 Length	9,300 cm
Package 1 Weight	40,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8,500 cm
Package 2 Width	10,000 cm
Package 2 Length	27,000 cm
Package 2 Weight	569,000 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30,000 cm
Package 3 Width	30,000 cm
Package 3 Length	40,000 cm
Package 3 Weight	6,380 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Profil cirkularnosti	 Informacije O Kraju Radnog Veka