

Tehničke karakteristike proizvoda

Karakteristike

A9S65292

switch disconnecter iSW - 2P - 125 A - 415 V



Osnovne informacije

Grupa proizvoda	Acti9
Ime proizvoda	Acti 9 iSW
Tip proizvoda ili komponente	Rastavljač
Kratko ime uređaja	iSW
Primena uređaja	Upravljanje Izolacija
Broj polova	2P
Kategorija upotrebe	AC-22A
Pogodno za izolaciju	Da

Dopunske informacije

[ie] nazivna struja	125 A pri 415 V AC 50/60 Hz
[ue] nazivni napon	415 V AC 50/60 Hz
[icm] nazivna kratkospojna moć uključenja	5 kA sam rastavljač
[icw] kratkotrajna podnosiva struja kratkog spoja	1500 A
[ui] nazivni napon izolacije	500 V AC 50/60 Hz
[uimp] nazivni podnosivi impulsni napon	6 kV
Tip upravljanja	Ručica
Lokalna signalizacija	ON/OFF očitavanje
Indikator pozicije kontakta	Da
Način montiranja	Fiksno
Nosači za montažu	DIN šina
Razvodni blok češljaste sabirnice	Gornji ili donji: DA
9 mm redovi	4
Visina	85 mm
Širina	36 mm
Dubina	73 mm
Boja	Bela
Mehanička trajnost	20000 ciklusa
Električna trajnost	2500 ciklusa
Povezivanje - priključci	Tunelski priključci (gornji ili donji) - $\leq 1 \times 50 \text{ mm}^2$ - kruti Tunelski priključci (gornji ili donji) - $\leq 1 \times 35 \text{ mm}^2$ - fleksibilni Tunelski priključci (gornji ili donji) - $\leq 1 \times 35 \text{ mm}^2$ - fleksibilni sa kablovskim završetkom
Dužina ogoljenog dela žice	9 mm
Moment pritezanja	3,5 N.m

Okruženje

Standardi	IEC 60947-3 EN 60947-3
Ip stepen zaštite	IP20
Stepen zaprljanosti	3
Tropikalizacija	2
Relativna vlažnost	95 % pri 55 °C

Temperatura okoline za rad uređaja	-25...60 °C
Temperatura okoline za skladištenje	-40...85 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,6 cm
Package 1 Width	7,5 cm
Package 1 Length	9,5 cm
Package 1 Weight	167,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	8,5 cm
Package 2 Width	10,0 cm
Package 2 Length	22,0 cm
Package 2 Weight	1,07 kg
Unit Type of Package 3	S03
Number of Units in Package 3	66
Package 3 Height	30,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	12,257 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	Da
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Učinak u vezi sa sadržajem halogena	Proizvod sa plastičnim delovima bez halogena

Ugovorna garancija

Garancija	18 months
-----------	-----------