

Tehničke karakteristike proizvoda

Karakteristike

GBY080005K

angular gearbox straight teeth GBY, Lexium,
80mm, reduction 5:1, 13arc.min, 67N.m



Osnovne informacije

Kompatibilnost grupe proizvoda	Lexium 32 Lexium SD3 Lexium 32i Lexium 62 ILM Lexium 62 Lexium ILS Lexium 52
Tip proizvoda ili komponente	Ugaoni planetarni reduktor
Tip reduktora	Ravni zubi
Kratko ime uređaja	GBY
Kompatibilnost proizvoda	BMI (70 mm, 2 BMI (70 mm, 3 BMH (70 mm, 3 BSH (70 mm, 3 BMH (100 mm, 1 BMH (100 mm, 2 BSH (100 mm, 1 BSH (100 mm, 2 BRS3 ILS (85 mm, 1 ILS (85 mm, 2 ILS (85 mm, 3 SH3 MH3 ILM
Spoljni prečnik reduktora	80 mm
Odnos redukcije	5:1

Dopunske informacije

Maksimalni torzioni zazor	13 arc.min
Torziona krutost	6 N.m/arcmin
Boja kućišta	Crna
Materijal kućišta	Crni anodizirani aluminijum
Materijal osovine	C 45
Dodatne informacije	Podmazan za životni vek
Servisni vek u satima	30000 sati pri 100 rpm pri 30 °C
Pozicija montiranja ručice	Bilo koja pozicija
Efikasnost	94 %
Maksimalna radijalna sila Fr	650 N pri 100 rpm, sila primenjena na srednjem rastojanju od izlaznog vratila tokom 30000 sati na 30 °C
Maksimalna osovinska sila Fa	1200 N pri 100 rpm, tokom 30000 sati na 30°C
Moment of inertia	0,869 kg.cm ²
Kontinuirani izlazni obrtni moment	67 N.m pri 100 rpm pri 30 °C
Maksimalni izlazni obrtni moment	107 N.m pri 100 rpm pri 30 °C
Masa proizvoda	4,4 kg
Input diameter	19,0 mm

Okruženje

Nivo buke	73 dB pri 1 m, bez opterećenja
Ip stepen zaštite	Izlaz osovine: IP54
Ambient temperature for operation	-25...90 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10,5 cm
Package 1 Width	10,0 cm
Package 1 Length	20,5 cm
Package 1 Weight	3,635 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm
Package 2 Weight	7,983 kg


Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Nema potrebe za namenskim operacijama recikliranja
Bez PVC	Da

Ugovorna garancija

Garancija	18 months
-----------	-----------

Dimensions with Servo Motor Adaptation Kit



- (1) GBK adaptation kit
(2) GBK adaptation kit related dimensions a1, c, Ø6, Ø7, Ø8 depend on the gearbox and servo motor combination
Ø8 shaft end adaptor in case motor shaft diameter is smaller than gearbox input coupling diameter

Values in mm

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5	a6
144	40	36	4	22.5	6	80	60 h7	20 h7	M6 x 10	70	88.3

Values in in.

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5	a6
5.67	1.57	1.42	0.15	0.88	0.23	3.15	2.36 h7	0.78 h7	M6 x 0.39	2.76	3.48