

Tehničke karakteristike proizvoda

Karakteristike

ISM20105P

OptiLine 45 - pole - tension-mounted - one-sided - polar white - 3500-3900 mm



Osnovne informacije

Range	OptiLine
Ime proizvoda	OptiLine 45
Kablovski instalacioni sistem	Stub
Product type	Stub
Tip stuba	Jednostrano
Završna obrada stuba/stubića	Presvučen prahom
Način montaže stuba	Napregnut

Dopunske informacije

Additional information	Podesivost plafonskih nosača 400 mm
Colour	Polarno bela (RAL 9003)
Veličina otvora sa prednje strane	45 mm
Materijal	Aluminijum presvučen prahom
Quantity package 1 / unit	Set od 1
Visina	3500...3900 mm
Dubina	89 mm
Širina	68 mm

Okruženje

Standardi	73/23/EEC 93/68/EEC EN 50085-1:2005 EN 60598-2-2 IEC 1084-2-4 NF C 68-102 SS 424 10 32
Operating temperature	-25...60 °C
Ip stepen zaštite	IP40

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	390,0 cm
Package 1 Width	6,8 cm
Package 1 Length	8,9 cm
Package 1 Weight	8,97 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Height	12,7 cm
Package 2 Width	15,5 cm
Package 2 Length	363,5 cm

Package 2 Weight	9,464 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	28
Package 3 Height	64,9 cm
Package 3 Width	120,0 cm
Package 3 Length	370,0 cm
Package 3 Weight	285,992 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	 REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)  EU RoHS deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda