

Tehničke karakteristike proizvoda Karakteristike

LAEN11 EasyPact TVS - pomoćni kontakti blok - 1 NO + 1 NC - vijčani priključci



Osnovne informacije

Grupa proizvoda	EasyPact
Kratko ime uređaja	LAEN
Tip proizvoda ili komponente	Pomoćni kontakti blok
Primena uređaja	Signalizacija
Boja	Grey (RAL 7011)

Dopunske informacije

Kompatibilnost grupe proizvoda	EasyPact TVS LC1E
Lokacija za montiranje	Prednji deo
Operacije pomoćnih kontakata	Trenutno
Raspored kontakata	1 NO + 1 NC
[ui] nazivni napon izolacije	690 V - for control circuit conforming to IEC 60947-5-1
[ue] nazivni radni napon	<= 690 V
[ith] dozvoljena termička struja u vazduhu	8 A (at 60 °C)
Irms nazivna moć uključenja	140 A AC u skladu sa IEC 60947-5-1
[icw] kratkotrajna podnosiva struja kratkog spoja	100 A - 1 s 120 A - 500 ms 140 A - 100 ms
Tip zaštite	GG osigurač 10 A
Mehanička trajnost	10 miliona ciklusa
Minimalna struja preklapanja	5 mA
Minimum switching voltage	17 V
Vreme nepreklapanja	1,5 Milisekundi pri zatvaranju bez preklapanja između NC i NO kontakta 1,5 milisekundi pri isključenju bez preklapanja između NC i NO kontakta
Otpornost izolacije	> 10 MOhm
Povezivanje - priključci	Control circuit: screw clamp terminals 1 1 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible with cable end Control circuit: screw clamp terminals 1 1 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible without cable end Control circuit: screw clamp terminals 2 2.5 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible with cable end Control circuit: screw clamp terminals 2 2.5 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible without cable end
Masa proizvoda	0,035 kg

Okruženje

Karakteristike životne sredine	Standardna sredina
Standardi	IEC 60947-5-1
Sertifikacija proizvoda	GOST
Ip stepen zaštite	IP20 u skladu sa IEC 60529
Zaštitni tretman	TH u skladu sa IEC 60068
Temperatura okoline za rad uređaja	-5...55 °C

Temperatura okoline za skladištenje	-60...80 °C
Nadmorska visina za rad uređaja	3000 m bez smanjenja karakteristika

Packing Units

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	34 g
Pakovanje 1 visina	2,4 cm
Pakovanje 1 širina	4,2 cm
Pakovanje 1 dužina	5 cm
Tip jedinice pakovanja 2	S02
Broj jedinica u pakovanju 2	100
Pakovanje 2 težina	3,751 kg
Pakovanje 2 visina	15 cm
Pakovanje 2 širina	30 cm
Pakovanje 2 visina	40 cm

Offer Sustainability

Propis REACH	REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------