



Osnovne informacije

Grupa proizvoda	TeSys
Ime proizvoda	TeSys D Green
Tip proizvoda ili komponente	Kontaktor
Kratko ime uređaja	LC1D
Primena kontaktora	Upravljanje motorom Rezistivno opterećenje
Kategorija upotrebe	AC-1 AC-3
Broj polova	3P
Power pole contact composition	3 NO
[ue] nazivni napon	Power circuit: ≤ 690 V AC 25...400 Hz
[ie] nazivna struja	25 A 60 °C) pri ≤ 440 V AC-1 za kolo napajanja 12 A 60 °C) pri ≤ 440 V AC-3 za kolo napajanja
Snaga motora kw	3 KW pri 220...230 V AC 50 Hz (AC-3) 5,5 KW pri 380...400 V AC 50 Hz (AC-3) 5.5 KW at 415 V AC 50 Hz (AC-3) 5.5 KW at 440 V AC 50 Hz (AC-3) 7.5 KW at 500 V AC 50 Hz (AC-3) 7,5 kW pri 660...690 V AC 50 Hz (AC-3)
Motor power HP (UL / CSA)	0.5 Hp at 115 V AC 60 Hz for 1 phase motors 2 Hp at 230/240 V AC 60 Hz for 1 phase motors 3 Hp at 200/208 V AC 60 Hz for 3 phases motors 3 Hp at 230/240 V AC 60 Hz for 3 phases motors 7.5 Hp at 460/480 V AC 60 Hz for 3 phases motors 10 hp at 575/600 V AC 60 Hz for 3 phases motors
Napon upravljačkog kola	48...130 V AC 50/60 Hz 48...130 V DC
Tip kalema	AC/DC elektronika
Sastav pomoćnog kontakta	1 NO + 1 NC
[uimp] nazivni podnosivi impulsni napon	6 kV conforming to IEC 60947
Kategorija prenapona	III
[ith] dozvoljena termička struja u vazduhu	10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit
Irms nazivna moć uključenja	250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Nazivna prekidna moć	250 A at 440 V for power circuit conforming to IEC 60947
[icw] kratkotrajna podnosiva struja kratkog spoja	100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit 30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit
Pripadajući osigurač	10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at ≤ 690 V coordination type 1 for power circuit 25 A gG at ≤ 690 V coordination type 2 for power circuit
Prosečna impedansa	2.5 mOhm - Ith 25 A 50 Hz for power circuit
[ui] nazivni napon izolacije	Power circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1
Električna trajnost	2,3 Miliona ciklusa 11 A AC-3 pri $U_e \leq 440$ V 0.8 Mcycles 25 A AC-1 at $U_e \leq 440$ V
Snaga disipacije po polu	1.56 W AC-1 0.36 W AC-3

Front cover	Sa
Nosači za montažu	Ploča Šina
Standardi	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Sertifikacije proizvoda	CCC CSA EAC UL KC DNV-GL LROS (Lloyds register of shipping)
Povezivanje - priključci	Control circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1... 4 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1... 2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 1... 4 mm ² solid Power circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 1... 4 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1... 2.5 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² solid Power circuit: screw clamp terminals 2 cable(s) 1... 4 mm ² solid
Moment pritezanja	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
Vreme uključenja/ isključenja	45...55 ms zatvaranje 20...90 ms otvaranje
Nivo sigurnosne pouzdanosti	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mehanička trajnost	15 Mcycles
Maksimalni radni ciklus	3600 cyc/h 60 °C

Dopunske informacije

Tehnologija kalema	Ugrađeno ograničenje u oba smera
Ograničenje napona upravljačkog kola	$\leq 0.1 U_c$ -40...70 °C propad napona AC/DC 0.85...1.1 U_c -40...60 °C u radu AC/DC 1...1.1 U_c 60...70 °C u radu AC/DC
Udar na snagu u va	25 VA 50/60 Hz 20 °C)
Udar na snagu u w	24 W pri 20 °C
Snaga držanja u va	1,3 VA 20 °C) 50/60 Hz
Snaga držanja u w	0,8 W pri 20 °C
Disipacija toplote	0,8 W pri 50/60 Hz
Tip pomoćnog kontakta	Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 Type mirror contact 1 NC conforming to IEC 60947-4-1
Frekvencija signalnog kola	25...400 Hz
Minimalna struja preklapanja	5 mA for signalling circuit
Minimalni napon preklapanja	17 V for signalling circuit

Vreme nepreklapanja	1.5 Ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Otpornost izolacije	> 10 MOhm for signalling circuit
Kompatibilnost	LC1D

Okruženje

Ip stepen zaštite	IP20 front face conforming to IEC 60529
Zaštitni tretman	TH conforming to IEC 60068-2-30
Stepen zaprljanosti	3
Temperatura okoline za rad	-40...60 °C 60...70 °C with derating
Temperatura okoline za skladištenje	-60...80 °C
Nadmorska visina za rad uređaja	0...3000 m
Otpornost na vatru	850 °C conforming to IEC 60695-2-1
Otpornost na plamen	V1 conforming to UL 94
Mehanička robusnost	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms
Visina	77 mm
Širina	45 mm
Dubina	86 mm
Masa proizvoda	0,373 kg
Boja	Siva (SE GREY 6) Zelena (SE GREEN 2)

Pakovanje

Pakovanje 1 težina	0,400 kg
--------------------	----------

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Informacije O Kraju Radnog Veka
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Učinak u vezi sa sadržajem halogena	Proizvod sa plastičnim delovima i kablovima bez halogena

Ugovorna garancija

Garancija	18 meseci
-----------	-----------