

LC1DT80AY7

TeSys D kontaktor - 4P(4 NO) - AC-1 - ≤ 440
V 80 A - 690 V AC 50/60 Hz kalem



Osnovne informacije

Grupa proizvoda	TeSys
Ime proizvoda	TeSys D
Tip proizvoda ili komponente	Kontaktir
Kratko ime uređaja	LC1D
Primena kontaktora	Rezistivno opterećenje
Kategorija upotrebe	AC-1
Broj polova	4P
Power pole contact composition	4 NO
[ue] nazivni napon	Power circuit: ≤ 690 V AC 25...400 Hz Power circuit: ≤ 300 V DC
[ie] nazivna struja	80 A (at ≤ 60 °C) at ≤ 440 V AC AC-1 for power circuit
Tip upravljačkog kola	AC at 50/60 Hz
Napon upravljačkog kola	690 V AC 50/60 Hz
Sastav pomoćnog kontakta	1 NO + 1 NC
[uimp] nazivni podnosivi impulsni napon	6 kV conforming to IEC 60947
Kategorija prenapona	III
[ith] dozvoljena termička struja u vazduhu	10 A (at 60 °C) for signalling circuit 80 A (at 60 °C) for power circuit
Irms nazivna moć uključenja	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1000 A at 440 V for power circuit conforming to IEC 60947
Nazivna prekidna moć	1000 A at 440 V for power circuit conforming to IEC 60947
[icw] kratkotrajna podnosiva struja kratkog spoja	520 A 40 °C - 10 s for power circuit 900 A 40 °C - 1 s for power circuit 110 A 40 °C - 10 min for power circuit 260 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Pripadajući osigurač	10 A gG for signalling circuit conforming to IEC 60947-5-1 125 A gG at ≤ 690 V coordination type 1 for power circuit 125 A gG at ≤ 690 V coordination type 2 for power circuit
Prosečna impedansa	1.6 mOhm - Ith 80 A 50 Hz for power circuit
[ui] nazivni napon izolacije	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 690 V conforming to IEC 60947-4-1
Električna trajnost	1.4 Mcycles 80 A AC-1 at $U_e \leq 440$ V
Snaga disipacije po polu	10.2 W AC-1
Front cover	Sa
Nosači za montažu	Šina Ploča

Standardi	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Sertifikacija proizvoda	CSA DNV GL UL BV CCC LROS (Lloyds register of shipping) GOST RINA
Povezivanje - priključci	Control circuit: screw clamp terminals 2 cable(s) 1... 2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1... 4 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1... 4 mm ² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1... 4 mm ² solid without cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm ² flexible without cable end Power circuit: EverLink BTR screw connectors 2 cable(s) 1...25 mm ² flexible without cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm ² flexible with cable end Power circuit: EverLink BTR screw connectors 2 cable(s) 1...25 mm ² flexible with cable end Kolo napajanja: EverLink BTR vijčani priključak 1 kabl(ovi) 1...35 mm ² jednožični bez kablovskog završetka Kolo napajanja: EverLink BTR vijčani priključak 2 kabl(ovi) 1...25 mm ² jednožični bez kablovskog završetka
Moment pritezanja	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 8 N.m - on screw clamp terminals - cable 25...35 mm ² hexagonal screw head 4 mm Power circuit: 5 N.m - on screw clamp terminals - cable 1...25 mm ² hexagonal screw head 4 mm
Vreme uključenja/isključenja	4...19 ms opening 12...26 ms closing
Nivo sigurnosne pouzdanosti	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mehanička trajnost	6 miliona ciklusa
Maksimalni radni ciklus	3600 cyc/h 60 °C

Dopunske informacije

Tehnologija kalema	Bez ugrađenog prigušivača
Ograničenje napona upravljačkog kola	0.3...0.6 Uc (-40...70 °C):drop-out AC 50/60 Hz 0.8...1.1 Uc (-40...60 °C):operational AC 50 Hz 0.85...1.1 Uc (-40...60 °C):operational AC 60 Hz 1...1.1 Uc (60...70 °C):operational AC 50/60 Hz
Udar na snagu u va	140 VA 60 Hz cos phi 0.75 (at 20 °C) 160 VA 50 Hz cos phi 0.75 (at 20 °C)
Snaga držanja u va	13 VA 60 Hz cos phi 0.3 (at 20 °C) 15 VA 50 Hz cos phi 0.3 (at 20 °C)
Disipacija toplote	4...5 W at 50/60 Hz
Tip pomoćnog kontakta	Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 Type mirror contact 1 NC conforming to IEC 60947-4-1
Frekvencija signalnog kola	25...400 Hz

Minimalna struja preklapanja	5 mA for signalling circuit
Minimalni napon preklapanja	17 V for signalling circuit
Vreme nepreklapanja	1.5 Ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Otpornost izolacije	> 10 MOhm for signalling circuit
Kompatibilnost kontakta	M6
Kompatibilnost	LC1D

Okruženje

Ip stepen zaštite	IP20 front face conforming to IEC 60529
Zaštitni tretman	TH conforming to IEC 60068-2-30
Stepen zaprljanosti	3
Temperatura okoline za rad	-40...60 °C 60...70 °C with derating
Temperatura okoline za skladištenje	-60...80 °C
Nadmorska visina za rad uređaja	0...3000 m
Otpornost na vatru	850 °C conforming to IEC 60695-2-1
Otpornost na plamen	V1 conforming to UL 94
Mehanička robusnost	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz Shocks contactor closed: 15 Gn for 11 ms Shocks contactor open: 10 Gn for 11 ms
Visina	122 mm
Širina	70 mm
Dubina	120 mm
Masa proizvoda	1,15 kg

Pakovanje

Pakovanje 1 težina	1,100 kg
Pakovanje 1 visina	0,750 dm
Pakovanje 1 širina	1,400 dm
Pakovanje 1 dužina	1,500 dm

Održivost ponude

Propis REACH	 REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Bez PVC	Da

Ugovorna garancija

Garancija	18 months
-----------	-----------