

Tehničke karakteristike proizvoda

Karakteristike

LC1F2254

TeSys F kontaktor - 4P(4 NO) - AC-1 - ≤ 440
V 315 A - bez kalema



Osnovne informacije

Grupa proizvoda	TeSys
Ime proizvoda	TeSys F
Tip proizvoda ili komponente	Kontaktör
Kratko ime uređaja	LC1F
Primena kontaktora	Rezistivno opterećenje
Kategorija upotrebe	AC-1
Broj polova	4P
Power pole contact composition	4 NO
[ue] nazivni napon	≤ 690 V AC 50/60 Hz
[ie] nazivna radna struja	315 A 40 °C) pri ≤ 440 V AC-1

Dopunske informacije

Napon upravljačkog kola	24...575 V AC 40...400 Hz sa LX9 kalemom 24...460 V DC with LX4 coil 100...250 V AC 50/60 Hz with LXE coil 100...380 V DC with LXE coil
[uimp] nazivni podnosivi impulsni napon	8 kV
Kategorija prenapona	III
[ith] dozvoljena termička struja u vazduhu	315 A (at 40 °C)
Irms nazivna moć uključenja	2250 A u skladu sa IEC 60947-4-1
Nazivna prekidna moć	1800 A conforming to IEC 60947-4-1
[icw] kratkotrajna podnosiva struja kratkog spoja	1800 A 40 °C - 10 s 1000 A 40 °C - 30 s 850 A 40 °C - 1 min 560 A 40 °C - 3 min 440 A 40 °C - 10 min
Pripadajući osigurač	315 A gG at ≤ 440 V
Prosečna impedansa	0.32 mOhm - lth 315 A 50 Hz
[ui] nazivni napon izolacije	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Snaga disipacije po polu	32 W AC-1
Ograničenje napona upravljačkog kola	U radu: 0.85...1.1 U_c AC 40...400 Hz Propad napona: 0.2...0.55 U_c AC 40...400 Hz Operational: 0.85...1.1 U_c DC with LX4 coil Drop-out: 0.15...0.2 U_c DC with LX4 coil Operational: 85...275 V AC 50/60 Hz with LXE coil Drop-out: 0...60 V AC 50/60 Hz with LXE coil Operational: 85...418 V DC with LXE coil Drop-out: 0...45 V DC with LXE coil
Disipacija toplote	8...9.8 W 2,2...2,5 W
Vreme uključenja/isključenja	35 ms zatvaranje za sa LX9 kalemom 130 ms otvaranje za sa LX9 kalemom 30...40 ms zatvaranje za sa LX4 kalemom 30...50 ms otvaranje za sa LX4 kalemom 40...80 ms closing for with LXE coil 6...54 ms opening for with LXE coil
Nosači za montažu	Ploča

Standardi	JIS C8201-4-1 IEC 60947-4-1 IEC 60947-1 EN 60947-4-1 EN 60947-1
Sertifikacija proizvoda	UL LR0S (Lloyds register of shipping) BV CB ABS DNV CSA RMRoS RINA
Povezivanje - priključci	Power circuit: lugs-ring terminals 1 cable(s) 185 mm ² Power circuit: connector 1 cable(s) 185 mm ² Power circuit: bar 2 cable(s) - busbar cross section: 32 x 4 mm Power circuit: bolted connection Control circuit: screw clamp terminals 1 cable(s) 1...4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² solid without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm ² Control circuit: screw clamp terminals 2 cable(s) 1...4 mm ² Control circuit: screw clamp terminals 1.0 cable(s) 0.2...2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.25...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.2...2.5 mm ² solid without cable end
Moment pritezanja	Power circuit: 35 N.m Control circuit: 1.2 N.m Control circuit: 0.6 N.m
Mehanička trajnost	10 miliona ciklusa
Udarna snaga u va	950...1180 VA, 40...400 Hz cos phi 0,9 (at 20 °C)sa LX9 kalemom 737...902 VA (at 20 °C)sa LX4 kalemom 280...310 VA, 50/60 Hz cos phi 0,5 (at 20 °C)sa LXE kalemom 270...320 VA (at 20 °C)sa LXE kalemom
Snaga držanja u va	8,9...10,9 VA 4,13...5,07 VA 4.5...7.0 VA, 50/60 Hz cos phi 0.5 (at 20 °C)with LXE coil 2.5...4.0 VA (at 20 °C)with LXE coil
Maksimalni radni ciklus	2400 cyc/h 55 °C
Kompatibilnost	LC1F

Okruženje

Ip stepen zaštite	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106
Zaštitni tretman	TH
Temperatura okoline za rad uređaja	-5...55 °C
Temperatura okoline za skladištenje	-60...80 °C
Dopustiva temperatura u okolini uređaja	-40...70 °C
Mehanička robusnost	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 5 Gn, 5...300 Hz Udara kontaktor nije u radu: 7 Gn za 1/2 sinusnog talasa (11 ms) Shocks contactor closed: 15 Gn for 1/2 sine wave (11 ms)
Visina	197 mm
Širina	208,5 mm
Dubina	181 mm
Masa proizvoda	5,55 kg

Pakovanje

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	5,58 kg
Pakovanje 1 visina	22 cm
Pakovanje 1 širina	24,5 cm
Pakovanje 1 dužina	27 cm
Pakovanje 2 težina	75,46 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	 REACH Deklaracija
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	 Informacije O Kraju Radnog Veka
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Bez PVC	Da

Ugovorna garancija

Garancija	18 meseci
-----------	-----------