

Tehničke karakteristike proizvoda

Karakteristike

LUB320

baza - TeSys U - 32 A - bez priključaka



Osnovne informacije

Grupa proizvoda	TeSys
Ime proizvoda	TeSys U
Kratko ime uređaja	LUB
Tip proizvoda ili komponente	Baza za aplikacije bez promene smera
Primena uređaja	Upravljanje motorima Zaštita motora
Broj polova	3P
Pogodno za izolaciju	Da
[ue] nazivni radni napon	690 V AC for power circuit
Frekvencija mreže	40...60 Hz
[ith] dozvoljena termička struja u vazduhu	32 A
[ie] nazivna radna struja	32 A at ≤ 440 V 23 A at 500 V 21 A at 690 V
Kategorija upotrebe	AC-44 AC-41 AC-43
[ics] servisna prekidna moć	50 KA at 230 V 50 KA at 440 V 10 KA at 500 V 4 kA at 690 V
Sastav pomoćnog kontakta	1 NO + 1 NC
Tip pomoćnog kontakta	Type linked contacts (1 NO + 1 NC) conforming to IEC 60947-4-1 Type mirror contact (1 NC) conforming to IEC 60947-1
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC 48...72 V AC 50/60 Hz 48...72 V DC 110...240 V AC 50/60 Hz 110...220 V DC

Informacije navedene u ovoj dokumentaciji predstavljaju opšti opis odnosno tehničke karakteristike performansi proizvoda. Dokumentacija nije namenjena da bude zamena za niti se može koristiti za određivanje prikladnosti i pouzdanosti proizvoda za specifičnu primenu. Dužnost je korisnika odnosno integratora da izvrši primerenu i sveobuhvatnu analizu rizika, procenu i proveru proizvoda u pogledu odgovarajuće specifične primene ili načina korišćenja. Ni Schneider Electric Industries SAS ni njegova povezana ili zavisna društva neće snositi odgovornost za zloupotrebu ovenavedenih informacija.

Dopunske informacije

Tipična potrošnja struje	200 MA at 24 V DC I maximum while closing with LUCM 220 MA at 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 220 MA at 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 25 MA at 110...220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 25 MA at 110...240 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD 280 MA at 110...220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 MA at 110...240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 MA at 48...72 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 MA at 48...72 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 45 MA at 48...72 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD 45 MA at 48...72 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 75 MA at 24 V DC I rms sealed with LUCM 80 MA at 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 90 mA at 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD
Disipacija toplote	3 W for control circuit with LUCA, LUCB, LUCC, LUCD 1.8 W for control circuit with LUCM
Nivo sigurnosne pouzdanosti	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Vreme uključenja/isključenja	35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM for control circuit 50 ms at ≥ 72 V closing with LUCA, LUCB, LUCC, LUCD for control circuit 60 ms at 48 V closing with LUCA, LUCB, LUCC, LUCD for control circuit 70 ms at 24 V closing with LUCA, LUCB, LUCC, LUCD for control circuit 65 ms closing with LUCM for control circuit
Mehanička trajnost	15 miliona ciklusa
Maksimalni radni ciklus	3600 ciklusa/h
Sertifikacija proizvoda	CE UL CSA CCC EAC ASEFA ATEX Marine
Standardi	EN 60947-6-2 IEC 60947-6-2 UL 60947-4-1, with phase barrier CSA C22.2 No 60947-4-1, with phase barrier
[ui] nazivni napon izolacije	690 V conforming to IEC 60947-6-2 (pollution degree 3) 600 V conforming to UL 60947-4-1 600 V conforming to CSA C22.2 No 60947-4-1
[uimp] nazivni podnosivi impulsni napon	6 kV conforming to IEC 60947-6-2
Bezbedno razdvajanje kola	400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1 appendix N 400 V SELV between the control or auxiliary circuit and the main circuit conforming to IEC 60947-1 appendix N
Način fiksiranja	Clipped (DIN rail) Screw-fixed (plate)
Povezivanje - priključci	Power circuit: screw clamp terminals 1 cable(s) 1...10 mm ² rigid Power circuit: screw clamp terminals 1 cable(s) 1...6 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 2.5...10 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 1...6 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1...6 mm ² rigid Power circuit: screw clamp terminals 2 cable(s) 1.5...6 mm ² flexible without cable end Control circuit: without connection
Moment pritezanja	Control circuit: 0.8...1.2 N.m flat screwdriver 5 mm Control circuit: 0.8...1.2 N.m Philips no 1 screwdriver 5 mm Power circuit: 1.9...2.5 N.m flat screwdriver 6 mm Power circuit: 1.9...2.5 N.m Philips No 2 screwdriver 6 mm
Širina	45 mm
Visina	154 mm
Dubina	126 mm

Masa proizvoda	0,865 kg
Kompatibilnost	LUB

Okruženje

Ip stepen zaštite	IP20 conforming to IEC 60947-1 (front panel and wired terminals) IP20 conforming to IEC 60947-1 (other faces) IP40 conforming to IEC 60947-1 (front panel outside connection zone)
Zaštitni tretman	TH u skladu sa IEC 60068
Temperatura okoline za rad	-25...60 °C with LUCM -25...70 °C with LUCA, LUCB, LUCC, LUCD
Temperatura okoline za skladištenje	-40...85 °C
Otpornost na vatru	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12
Nadmorska visina za rad	2000 m
Otpornost na udare	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27
Otpornost na vibracije	2 gn (f= 5...300 Hz) power poles open conforming to IEC 60068-2-27 4 gn (f= 5...300 Hz) power poles closed conforming to IEC 60068-2-27
Otpornost na elektrostatičko pražnjenje	8 KV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2
Otpornost na elektromagnetno polje	10 V/m 3 conforming to IEC 61000-4-3
Otpornost na brze prelaze	2 KV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4
Nerasut udarni talas	1 KV serial mode 24...240 V AC conforming to IEC 60947-6-2 1 KV serial mode 48...220 V DC conforming to IEC 60947-6-2 2 KV common mode 24...240 V AC conforming to IEC 60947-6-2 2 kV common mode 48...220 V DC conforming to IEC 60947-6-2
Otpornost na elektromagnetna polja	10 V conforming to IEC 61000-4-6
Otpornost na mikroprekide	3 ms for control circuit
Imunost na propade napona	70 % / 500 ms conforming to IEC 61000-4-11

Pakovanje

Pakovanje 1 težina	0,828 kg
Pakovanje 1 visina	1,720 dm
Pakovanje 1 širina	0,570 dm
Pakovanje 1 dužina	1,450 dm

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	REACh Deklaracija
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Informacije O Kraju Radnog Veka
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Bez PVC	Da

Ugovorna garancija

Garancija	18 meseci
-----------	-----------