

Lista sa podacima o proizvodima

Specifikacije



standardno MKS okidač, Compact NSXm, nazivni napon 24 VDC, 24 VAC 50/60Hz

LV426841

Cena* bez PDV-a: 10.908,00 RSD

Osnovne informacije

Grupa proizvoda	Compact
Grupa proizvoda	ComPacT NSXm nova generacija
Kratko ime uređaja	MX
Tip proizvoda ili komponente	Naponski okidač
Primena uređaja	Upravljanje
Tip naponskog okidača	Kalem za isključenje Okidač za isključenje
Tip upravljanja	Standardni
Napon upravljačkog kola	24 V AC 50/60 Hz 24 V DC
Kompatibilnost grupe proizvoda	Compact ComPacT NSXm nova generacija Compact Compact NSXm PowerPact PowerPact B

Dopunske informacije

Operating threshold	0.7 Un otvaranje
Vreme odziva	< 50 ms
Tip kontrolnog signala	Impuls Držanje
Trajanje impulsa	>= 20 ms
Pomoćni priključni blok	Opruga

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,500 cm
Package 1 Width	5,700 cm
Package 1 Length	6,300 cm
Package 1 Weight	60,400 g
Unit Type of Package 2	S03
Number of Units in Package 2	120
Package 2 Height	30,000 cm
Package 2 Width	30,000 cm
Package 2 Length	40,000 cm

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

Package 2 Weight

7,648 kg

Environmental Data

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

Ekološki otisak

Emisija ugljenika (kg CO2 eq.)

1

Izjava o zaštiti okoline

[Profil ekološke prihvatljivosti proizvoda](#)

Use Better

Materijali i pakovanje

Sadržaj recikliranog metala

0

Pakovanje sa recikliranim kartonom

Da

Pakovanje bez plastike

Da

[EU RoHS direktiva](#)

Usaglašeno sa izuzecima

SCIP broj

75582d60-9779-4641-a03b-18e996230a58

Uredba REACH

[REACH deklaracija](#)

Performanse sadržaja halogena

Proizvod sadrži halogen iznad dozvoljenog nivoa

Bez silikona

Ne

Use Again

Prepakovanje i prefabrikovanje

Profil cirkularnosti

[Informacije o kraju radnog veka](#)

Povraćaj

No

WEEE



Proizvod se mora odložiti na tržišta Evropske unije nakon posebnog sakupljanja otpada i nikada ne završiti u kanti za smeće.

Offer Marketing Illustration

Product benefits / Features



Compact NSXm
Range Accessories

Wireless indication auxiliary

Long terminal shield

Standard auxiliary contact

Rotary handles

Inter-phase barrier

Toggle padlocking device

MN undervoltage release

Standard MX shunt release

The image displays a collection of accessories for the Compact NSXm circuit breaker range. At the top left, a green circular graphic contains a small image of the main circuit breaker. Below this, the title 'Compact NSXm Range Accessories' is prominently displayed. The accessories are arranged in three rows. The first row includes a 'Wireless indication auxiliary' (a green module), a 'Long terminal shield' (a grey and black component), and a 'Standard auxiliary contact' (a black component). The second row features 'Rotary handles' (two black handles) and an 'Inter-phase barrier' (a black barrier). The third row shows a 'Toggle padlocking device' (a black device), an 'MN undervoltage release' (a black component), and a 'Standard MX shunt release' (a black component).

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm

Moulded Case Circuit Breaker



Efficiency
It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.

Reliability
optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.

Connectivity
Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

Offer Marketing Illustration

Product benefits / Features



Compact NSX
Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents: 16 to 160 A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- EverLink™ connectors for bare cables