

Tehničke karakteristike proizvoda Karakteristike

MTN6810-0102

SpaceLogic KNX Universal Dimming, Extension 2 channel



Osnovne informacije

Grupa proizvoda	SpaceLogic KNX
Tip proizvoda ili komponente	Aktuator dimovanja
Način rada	KNX sistem sabirnice
Tip komunikacije	KNX

Dopunske informacije

Nosači za montažu	DIN šina
[ue] nazivni napon	230 V
Mrežna frekvencija	50/60 Hz
Broj izlaza	2
Tip opterećenja	Inkandescentna sijalica: 20...350 W pri 230 V Halogena sijalica: 20...350 W pri 230 V LV halogen: 20...350 W pri 230 V RC LED lampa: 2...200 W pri 230 V RL LED lampa: 2...60 W pri 230 V

Okruženje

Ip stepen zaštite	IP20
-------------------	------

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8,100 cm
Package 1 Width	12,600 cm
Package 1 Length	15,900 cm
Package 1 Weight	260,000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30,000 cm
Package 2 Width	40,000 cm
Package 2 Length	60,000 cm
Package 2 Weight	7,994 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
EU RoHS direktiva	У складу са изузецима
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	 Informacije O Kraju Radnog Veka

Ugovorna garancija

Garancija	18 months
-----------	-----------