

Tehničke karakteristike proizvoda

Karakteristike

NSYPTDS1

Spacial - set za spoljašnju ugradnju
frekventnog regulatora - Altivar Process
veličina S1 - IP55



Osnovne informacije

Grupa proizvoda	Spacial
Tip proizvoda ili komponente	Set za ugradnju frekventnog regulatora van ormara
Accessory category	Pribor za montažu
Specifične primene proizvoda	Procesi i komunalna preduzeća
Kompatibilnost grupe proizvoda	Spacial SF i SM orman 400 mm x 300 mm Spacial S3D orman 400 mm x 300 mm Altivar variable speed drive ATV630 Altivar variable speed drive ATV930
Compatibility for Altivar Process 630-930, size:	1
Snaga motora kW	0,75 KW 220/240 V 1,5 KW 220/240 V 2,2 KW 220/240 V 3 KW 220/240 V 4 KW 220/240 V 0,75 KW 380/480 V 1,5 KW 380/480 V 2,2 KW 380/480 V 3 KW 380/480 V 4 KW 380/480 V 5,5 KW 380/480 V
Lokacija montaže	Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure
Sastav seta	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic.

Dopunske informacije

Dopustivo trajno opterećenje	4,8 kg
Boja	Grey (RAL 7035)
Visina	360 Mm spoljašnja: 307 mm otvor:
Širina	235 Mm spoljašnja: 190 mm otvor:
Dubina	22 mm odvajanje ormara od zida:
Masa proizvoda	1,58 kg
Servisi	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

Okruženje

Ip stepen zaštite	IP55 u skladu sa IEC 60529
-------------------	----------------------------

Pakovanje

Pakovanje 1 težina	1,565 kg
--------------------	----------

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)  EU RoHS deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda