

# Product datasheet

Specifications



Emergency luminaire, Exiway  
Smartled, Activa/Dicube, selectable  
duration, 800lm, cold temperature,  
IP65, white

OVA48526

## Main

Range	Exiway
product name	Exiway Smartled Dicube
Product or component type	Emergency luminaire
Device application	Anti-panic lighting
Function	Addressable Self-test
Operational mode	Non-maintained Maintained
Number of batteries	1 x 6.4 V 3.35 Ah LiFePO4
Colour tint	White
Light source	LED
Visibility distance	24 m 30 m
Wiring device additional information	Pictograms to be ordered separately

## Complementary

Mounting support	Wall Ceiling False ceiling
[Ue] rated operational voltage	230 V AC 50/60 Hz
Power consumption in VA	6 VA non-maintained 13.6 VA maintained
Power consumption in W	0.4 W non-maintained 4.9 W maintained
Electrical insulation class	Class II
LED lifespan	100000 h
Test function	Automatic periodical functional & duration test
Autonomy	1 h 1.5 h 2 h 3 h
Charging time	12 h
Luminous flux	Emergency condition: 800 lm for 1 h Emergency condition: 560 lm for 1.5 h Emergency condition: 450 lm for 2 h Emergency condition: 330 lm for 3 h Maintained mode: 500 lm
Type of glass	Serigraphed transparent glass

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	LED
Material	Polycarbonate self-extinguishing
Height	127 mm
Depth	45.5 mm
Width	300 mm
Product weight	650 g

## Environment

IP degree of protection	IP65
IK degree of protection	IK07
Fire resistance	850 °C
Ambient air temperature for operation	-25...40 °C
Standards	EN 60598-2-22: II EN 62471 EN 62034 EN 60598-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.900 cm
Package 1 Width	13.300 cm
Package 1 Length	30.900 cm
Package 1 Weight	820.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.940 kg

## Contractual warranty

Warranty	60 Months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	38
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
REACH Regulation	<a href="#">REACH Declaration</a>

Use Again


Repack and remanufacture	
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	Yes
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

