

## Tehničke karakteristike proizvoda Karakteristike

## SRVS6KI

Schneider Electric Easy UPS SRV 6000VA  
230V



### Pregled

Prezentacija	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Vreme isporuke	Usually in Stock

### Opšte

Obezbeđena oprema	Basic UPS signalling RS-232 cable CD with software User manual USB cable
Number of tare power	60 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

### Fizički

Boja	Black
Dubina	37,4 cm
Visina	68,5 cm
Masa proizvoda	54 kg
USB kompatibilno	Yes
Širina	19 cm

### Ulaz

Frekvencija mreže	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Ograničenje napona ulaza	100...280 V adjustable (half load) 160...280 V
Inputvoltage_other	220 V 240 V
Naponski ulaz	230 V

## Izlaz

Nazivna snaga u W	6000 W
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvoltage_other	220 V 240 V
Mera talasnosti	3 : 1
UPS type	Dvostruka online konverzija
Wave type	Sinusni talas
Output connector type	Hard wire 3-wire (H N + E) 1
Tip bypass-a	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efikasnost	94 % (full load)
Graph display	2
Half load runtime	00:10:00 3000 W
Output voltage	230 V
Maximum configurable power in VA	6000 VA
Nazivna snaga u va	6000 VA

## Usklađenost

Sertifikacija proizvoda	CE
Standardi	IEC 62040-1-1 IEC 62040-1-2

## Okolina

Temperatura okoline za rad uređaja	0...40 °C
Relativna vlažnost	0...95 % non-condensing
Nadmorska visina za rad	0...3000 m
Temperatura okoline za skladištenje	-15...60 °C
Storage Relative Humidity	0...95 % Bez kondenzacije
Nadmorska visina skladištenja	0...15000 m
Nivo zvuka	55 dB
Show note OP temperature	No
IP stepen zaštite	IP20

## Baterija i runtime

Tip baterije	Olovna baterija
Number of battery filled slots	0
Number of battery free slots	0
Dodatne informacije	Podesivo za izlazni napon 220 : 230 ili 240
Liquid value	0
Battery curve	D
Battery charger power	112400 W nazivno

### Komunikacija i upravljanje

Slobodni slotovi	1
Control panel	Multifunkcionalni LCD status i upravljačka konzola
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Da

### Prenaponska zaštita i filtriranje

Surge energy rate	600 J
-------------------	-------

### Packing Units

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	66 kg
Pakovanje 1 visina	91 cm
Pakovanje 1 širina	29 cm
Pakovanje 1 dužina	49,5 cm

### Ugovorna garancija

Garancija	2 years repair or replace
-----------	---------------------------