

Tehničke karakteristike proizvoda

Karakteristike

SRVS6KRIRK

SE Easy UPS SRVS RM 6000VA 230V,
sa setom za ugradnju u rek, sa spoljašnjim
baterijskim modulom



Pregled

Prezentacija	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Vreme isporuke	Usually in Stock

Opšte

Obezbeđena oprema	Basic UPS signalling RS-232 cable CD with software Rack mounting brackets Rack mounting support rails User manual USB cable
Number of tare power	60 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Fizički

Broj jedinice reka	4U
Boja	Black
Dubina	61,5 cm
Visina	17,3 cm
Masa proizvoda	61 kg
USB kompatibilno	Yes
Širina	43,8 cm

Ulaz

Frekvencija mreže	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Ograničenje napona ulaza	100...280 V adjustable (half load) 160...280 V
Inputvolt_other	220 V 240 V
Naponski ulaz	230 V

Izlaz

Nazivna snaga u W	6000 W
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvoltage_other	220 V 240 V
Mera talasnosti	3 : 1
UPS type	Dvostruka online konverzija
Wave type	Sinusni talas
Output connector type	Hard wire 3-wire (H N + E) 1
Tip bypass-a	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efikasnost	94 % (full load)
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	6000 VA
Nazivna snaga u va	6000 VA

Usklađenost

Sertifikacija proizvoda	CE
Standardi	IEC 62040-1-1 IEC 62040-1-2

Okolina

Temperatura okoline za rad uređaja	0...40 °C
Relativna vlažnost	0...95 % non-condensing
Nadmorska visina za rad	0...3000 m
Temperatura okoline za skladištenje	-15...60 °C
Storage Relative Humidity	0...95 % Bez kondenzacije
Nadmorska visina skladištenja	0...15000 m
Nivo zvuka	55 dB
Show note OP temperature	No
IP stepen zaštite	IP20

Baterija i runtime

Tip baterije	Olovna baterija
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 sati
Dodatne informacije	Podesivo za izlazni napon 220 : 230 ili 240
Liquid value	0
Battery curve	D
Battery charger power	373 W nazivno

Komunikacija i upravljanje

Slobodni slotovi	1
Control panel	Multifunkcionalni LCD status i upravljačka konzola
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Da

Prenaponska zaštita i filtriranje

Surge energy rate	600 J
-------------------	-------

Packing Units

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	71 kg
Pakovanje 1 visina	48,5 cm
Pakovanje 1 širina	60 cm
Pakovanje 1 dužina	83,6 cm
Tip jedinice pakovanja 2	P12
Broj jedinica u pakovanju 2	1
Pakovanje 2 težina	83,001 kg
Pakovanje 2 visina	37 cm
Pakovanje 2 širina	80 cm
Pakovanje 2 visina	120 cm

Ugovorna garancija

Garancija	2 years repair or replace
-----------	---------------------------