

Tehničke karakteristike proizvoda

Karakteristike

TPSAUX43

auxiliary contact, TransferPacT, indication for source I and source II, frame 250A, frame 630A



Osnovne informacije

Grupa proizvoda	TransferPacT
Tip proizvoda ili komponente	Auxiliary Contact Module
Primena uređaja	Signalizacija

Dopunske informacije

Sastav pomoćnog kontakta	2 NO + 2 NC
Signalna funkcija	Switch position (SI and SII)
Pomoćni priključni blok	Opruga 0,5...1,5 mm ² (AWG 20...AWG 16)
Način montiranja	Sistemom na klik
Pozicija montiranja ručice	Inside front cover
[I _{th}] dozvoljena termička struja u vazduhu	5 A
Minimalno opterećenje	100 mA pri 24 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Kompatibilnost proizvoda	TA25 TR25 TA63 TR63
Pribor / posebna kategorija	Pribor za signalizaciju

Okruženje

Ip stepen zaštite	IP20
Stepen zaprljanosti	3

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,500 cm
Package 1 Width	7,000 cm
Package 1 Length	7,500 cm
Package 1 Weight	34,000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15,000 cm
Package 2 Width	30,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	634,000 g

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
EU RoHS direktiva	У складу са изузецима
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	 Informacije O Kraju Radnog Veka