

Tehničke karakteristike proizvoda

Karakteristike

TPSAUX44

auxiliary contact, TransferPacT, indication for
OFF position, frame 250A, frame 630A



Osnovne informacije

Grupa proizvoda	TransferPacT
Tip proizvoda ili komponente	Auxiliary Contact Module
Primena uređaja	Signalizacija

Dopunske informacije

Sastav pomoćnog kontakta	2 NO + 2 NC
Signalna funkcija	Switch position (off)
Pomoćni priključni blok	Opruga 0,5...1,5 mm ² (AWG 20...AWG 16)
Način montiranja	Sistemom na klik
Pozicija montiranja ručice	Inside front cover
[I _{th}] dozvoljena termička struja u vazduhu	5 A
Minimalno opterećenje	100 mA pri 24 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Kompatibilnost proizvoda	TA25 TR25 TA63 TR63
Pribor / posebna kategorija	Pribor za signalizaciju

Okruženje

Ip stepen zaštite	IP20
Stepen zaprljanosti	3

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,700 cm
Package 1 Width	7,000 cm
Package 1 Length	7,700 cm
Package 1 Weight	38,000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15,000 cm
Package 2 Width	30,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	658,000 g

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
EU RoHS direktiva	У складу са изузецима
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	 Informacije O Kraju Radnog Veka