



Osnovne informacije

Tip proizvoda ili komponente	Motorna prigušnica
Kompatibilnost grupe proizvoda	Altivar 61Q Altivar 71Q Altivar 212 Altivar 71 Altivar Process ATV600 Altivar Process ATV900 Altivar 61
Specifične primene proizvoda	Izlazni filter
[in] nazivna struja	215 A

Kompatibilnost proizvoda	ATV61HD11N4
	ATV61HD15N4
	ATV61HD18N4
	ATV61HU22S6X
	ATV61HU30S6X
	ATV61HU40S6X
	ATV61HU55N4
	ATV61HU55S6X
	ATV61HU75N4
	ATV61HU75S6X
	ATV61WD11N4
	ATV61WD11N4C
	ATV61WD15N4
	ATV61WD15N4C
	ATV61WD18N4
	ATV61WD18N4C
	ATV61WU55N4
	ATV61WU55N4C
	ATV61WU75N4
	ATV61WU75N4C
	ATV71HD11N4
	ATV71HD11Y
	ATV71HD15N4
	ATV71HD18N4
	ATV71HU15S6X
	ATV71HU22S6X
	ATV71HU30S6X
	ATV71HU40S6X
	ATV71HU55N4
	ATV71HU55S6X
	ATV71HU75N4
	ATV71HU75S6X
	ATV71PD11N4Z
	ATV71PU55N4Z
	ATV71PU75N4Z
	ATV71WD11N4
	ATV71WD15N4
	ATV71WD18N4
	ATV71WU55N4
	ATV71WU75N4
	ATV212HU15N4
	ATV61HD15Y
	ATV61HD18Y
	ATV61HD22N4
	ATV61HD22Y
	ATV61HD30N4
	ATV61HD30Y
	ATV61HD37N4
	ATV61WD22N4
	ATV61WD22N4C
	ATV61WD30N4
	ATV61WD30N4C
	ATV61WD37N4
	ATV61WD37N4C
	ATV71HD15Y
	ATV71HD18Y
	ATV71HD22N4
	ATV71HD22Y
	ATV71HD30Y
	ATV71HD37N4
	ATV71WD30N4
	ATV71WD37N4
	ATV630 frekventni regulator - 2,2 kW, 500...690 V trofazno
	ATV630 frekventni regulator - 3 kW, 500...690 V trofazno
	ATV630 frekventni regulator - 4 kW, 500...690 V trofazno
	ATV630 frekventni regulator - 5,5 kW, 500...690 V trofazno
	ATV630 frekventni regulator - 7,5 kW, 500...690 V trofazno
	ATV630 frekventni regulator - 11 kW, 500...690 V trofazno
	ATV930 frekventni regulator - 2,2 kW, 500...690 V trofazno
	ATV930 frekventni regulator - 3 kW, 500...690 V trofazno
	ATV930 frekventni regulator - 4 kW, 500...690 V trofazno
	ATV930 frekventni regulator - 5,5 kW, 500...690 V trofazno
	ATV930 frekventni regulator - 7,5 kW, 500...690 V trofazno
	ATV930 frekventni regulator - 11 kW, 500...690 V trofazno

Nedded quantity	3
Električna veza	Konektor M10

Dopunske informacije

Maksimalna dužina kabla motora	150 M oklopljen kabl P motora 30...45 kW pri 200...240 V 1 300 M neoklopljen kabl P motora 30...45 kW pri 200...240 V 1 200 M oklopljen kabl P motora 5,5...18,5 kW pri 380...480 V 1 300 M neoklopljen kabl P motora 5,5...18,5 kW pri 380...480 V 1 150 M oklopljen kabl P motora 22...30 kW pri 380...480 V 1 300 M neoklopljen kabl P motora 22...30 kW pri 380...480 V 1 150 M oklopljen kabl P motora 45...75 kW pri 380...480 V 1 300 M neoklopljen kabl P motora 45...75 kW pri 380...480 V 1 150 M oklopljen kabl P motora 2,2...7,5 kW pri 500...600 V 1 250 M neoklopljen kabl P motora 2,2...7,5 kW pri 500...600 V 1 250 M oklopljen kabl P motora 2,2...7,5 kW pri 500...600 V 2 400 M neoklopljen kabl P motora 2,2...7,5 kW pri 500...600 V 2 100 M oklopljen kabl P motora 2,2...30 kW pri 500...690 V 2 150 M neoklopljen kabl P motora 2,2...30 kW pri 500...690 V 2 150 M oklopljen kabl P motora 11...30 kW pri 500...690 V 2 250 M neoklopljen kabl P motora 11...30 kW pri 500...690 V 2 150 M oklopljen kabl P motora 30...160 kW pri 500...690 V 1 250 M neoklopljen kabl P motora 30...160 kW pri 500...690 V 1 250 M oklopljen kabl P motora 30...160 kW pri 500...690 V 2 300 M neoklopljen kabl P motora 30...90 kW pri 500...690 V 2 400 M neoklopljen kabl P motora 90...160 kW pri 500...690 V 2 200 M oklopljen kabl P motora 37 kW pri 380...480 V 1 300 M neoklopljen kabl P motora 37 kW pri 380...480 V 1 200 M oklopljen kabl P motora 90 kW pri 380...480 V 1 300 m neoklopljen kabl P motora 90 kW pri 380...480 V 1
Du/dt	500 V/μs maksimalno pri 400 V 750 V/μs maksimalno pri 500 V 1000 V/μs maksimalno pri 690 V
Termički gubici	430 W
Maximum drive output frequency	100 Hz
Temperatura okoline za rad	-10...50 °C
Masa proizvoda	15,5 kg

Okruženje

Ip stepen zaštite	IP20 (sa setovima VW3A9612,613) IP00
Temperatura okoline za skladištenje	-25...70 °C

Pakovanje

Pakovanje 1 težina	17,069 kg
Pakovanje 1 visina	2,900 dm
Pakovanje 1 širina	3,850 dm
Pakovanje 1 dužina	2,800 dm

Održivost ponude

Propis REACH	 REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)  EU RoHS deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu

Ugovorna garancija

Garancija	18 meseci
-----------	-----------