

Tehničke karakteristike proizvoda

Karakteristike

VW3M5A22R25

Servo motor BCH16 napojni kabl, 6G2.0, 25M,
neoklopljeni, MIL, kočnica



Osnovne informacije

Grupa proizvoda	Lexium
Pribor / posebna kategorija	Pribor za povezivanje
Pribor / posebni tip	Kabl napajanja
Tip proizvoda ili komponente	Kabl
Pribor / posebna namena	Od servo motora do servo pogona
Sastav kabla	6 x 2.0 mm ²

Dopunske informacije

Kompatibilnost proizvoda	Servo motor BCH16 130 mm, 0,85 kW, with brake Servo motor BCH16 100 mm, 1 kW, with brake Servo motor BCH16 130 mm, 1 kW, with brake Servo motor BCH16 130 mm, 1,5 kW, with brake Servo regulator LXM16D, 1 kW, 200...230 V Servo regulator LXM16D, 1,5 kW, 200...230 V
Električna veza	1 konektor 7-pole MIL female connector 7 pin(ovi) 2 kraja sa slobodnim žicama lugs 6 pin(ovi)
Kompatibilnost grupe proizvoda	Easy Lexium 16
Tip kabla	Neoklopljen kabl
Dužina kabla	25 m
Masa proizvoda	4,0 kg

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	36,0 cm
Package 1 Width	27,0 cm
Package 1 Length	9,0 cm
Package 1 Weight	6,215 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30,0 cm
Package 2 Width	40,0 cm
Package 2 Length	60,0 cm
Package 2 Weight	13,19 kg