

# Lista sa podacima o proizvodima

Specifikacije



Kompletno taster dugme za hitno isključivanje, Easy Harmony XA2, plastična glava, 22mm, okretanjem za otpuštanje, 30mm, 1NC, crvena

XA2AS442

## Osnovne informacije

Grupa proizvoda	Easy Harmony XA2
Kratko ime uređaja	XA2
Tip proizvoda ili komponente	Kompletni taster za nužno isključenje
Prezentacija uređaja	Kompletni proizvod
Ime komponente	XA2A
Materijal podnožja	Plastika
Prečnik za montiranje	22,5 mm
Prodaja po nedeljivim količinama	1

## Dopunske informacije

Radni položaj	Bilo koja pozicija
Montaža uređaja	Otvor za montažu - prečnik: 22,5 mm
Centar za fiksiranje	$\geq 30 \times 40$ mm (panel) 1...5 mm
Način fiksiranja	Maticom za fiksiranje preporučeni moment: 2,2 N.m (+/- 0.2 N.m)
Oblik glave signalne jedinice	Okrugla
Reset	Otpuštanje zakretanjem
Profil glave uređaja	Crvena pečurkasti taster $\varnothing 30$ mm
Boja kapica/glave ili sočiva	Crvena
Tip kontakata i sastav	1 NC
Operacija kontakata	Sporo isključenje
Pozitivno otvaranje	Sa NC kontaktom
Mehanička trajnost	100000 ciklusa
Povezivanje - priključci	Vijčani priključni blok, $\leq 2 \times 1.5$ mm <sup>2</sup> Vijčani priključni blok, $\leq 1 \times 2.5$ mm <sup>2</sup> Vijčani priključni blok, $\geq 1 \times 0.5$ mm <sup>2</sup> Faston priključci 6.3 mm
Moment pritezanja	0,8...1,2 N.m
Zaštita od kratkog spoja	10 A gL osigurač u skladu sa IEC 60269-1
[ui] nazivni napon izolacije	600 V u skladu sa IEC 60947-1
[uimp] nazivni podnosivi impulsni napon	6 kV u skladu sa IEC 60947-1
[ie] nazivna radna struja	3 A pri 240 V, AC-15, A600 0,27 A pri 250 V, DC-13, Q600

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

<b>Električna trajnost</b>	500000 ciklusa, AC-15, 3 A pri 575 V, broj operacija <60 ciklusa/min, faktor opterećenja: 0,5 u skladu sa IEC 60947-5-1 500000 ciklusa, DC-13, 0,2 A pri 110 V, broj operacija <60 ciklusa/min, faktor opterećenja: 0,5 u skladu sa IEC 60947-5-1
<b>Električna pouzdanost iec 60947-5-4</b>	$\Lambda < 10\exp(-8)$ pri 24 V, 5 mA u skladu sa IEC 60947-5-4
<b>Visina</b>	43 mm
<b>Širina</b>	30 mm
<b>Dubina</b>	74,0 mm
<b>masa proizvoda</b>	0,047 kg
<b>Tip ručice</b>	Otpuštanje zakretanjem

## Okruženje

<b>Tretman zaštite</b>	TC
<b>Temperatura okoline za skladištenje</b>	-40...70 °C
<b>Temperatura okoline za rad uređaja</b>	-25...55 °C
<b>Kategorija prenapona</b>	Klasa I conforming to IEC 536
<b>Ip stepen zaštite</b>	IP65 conforming to IEC 60068-2-27
<b>Ik stepen zaštite</b>	IK07
<b>Standardi</b>	GB 14048.1 IEC 60947-1 IEC 60947-5-1 GB 14048.5
<b>Sertifikacija proizvoda</b>	programabilan kao logički ulaz sprovedene i zračene emisije sa najpasom predgrevanje
<b>Otpornost na vibracije</b>	5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6
<b>Otpornost na udare</b>	50 gn (trajanje = 11 milisekundi) za ubrzanje polovine sinusne periode u skladu sa IEC 60068-2-27 30 gn (trajanje = 18 milisekundi) za ubrzanje polovine sinusne periode u skladu sa IEC 60068-2-27

## Pakovanje

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7,4 cm
<b>Package 1 Width</b>	4 cm
<b>Package 1 Length</b>	4,3 cm
<b>Package 1 Weight</b>	47 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	5
<b>Package 2 Height</b>	3 cm
<b>Package 2 Width</b>	12 cm
<b>Package 2 Length</b>	60 cm
<b>Package 2 Weight</b>	240 g
<b>Unit Type of Package 3</b>	S02
<b>Number of Units in Package 3</b>	100

Package 3 Height	15 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5,25 kg

## Ugovorna garancija

Garancija (u mesecima)	18
------------------------	----

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

### Ekološki otisak

Ukupan životni vek ugljeničnog otiska	0.6 kg CO2 eq.
Ugljenični otisak faze proizvodnje [A1–A3]	0.4 kg CO2 eq.
Ugljenični otisak faze distribucije [A4]	0 kg CO2 eq.
Ugljenični otisak faze instalacije [A5]	0 kg CO2 eq.
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	0.1 kg CO2 eq.
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	0.1 kg CO2 eq.
Izjava o zaštiti okoliša	<a href="#">Profil ekološke prihvatljivosti proizvoda</a>

### Use Better

#### Materijali i pakovanje

Pakovanje sa recikliranim kartonom	Da
Pakovanje bez plastike	Ne
Direktiva RoHS	<a href="#">Usaglašeno</a>
Uredba REACH	<a href="#">Referenca ne sadrži SVHC iznad propisanog praga</a>

### Use Longer

#### Produženje trajanja veka

Popravka	Ne
----------	----


### Use Again

#### Prepakovanje i prefabrikovanje

Potencijal za recikliranje, u %	33
Profil cirkularnosti	<a href="#">Informacije o kraju radnog veka</a>
Povraćaj	No


Dimensions Drawings

Dimensions



e : Clamping thickness : 1 to 5 mm/0.04 to 0.20 in.

Head Dimension



Mounting and Clearance

Panel Cut-Out


---



Connections and Schema

Wiring Diagram

---




8.0 mm	0.5...2.5 mm <sup>2</sup>	0.5...1.5 mm <sup>2</sup>
0.32 in.	20...14 AWG	20...16 AWG

Wiring tightening torque : 0.8 ... 1.2 Nm (7 ... 10.6 lb-in)

Technical Illustration

Dimensions



Technical Illustration

Wiring diagram



8.0 mm	0.5...2.5 mm <sup>2</sup>	0.5...1.5 mm <sup>2</sup>
0.32 in.	20...14 AWG	20...16 AWG

		Nm	0.8...1.2
		lb-in	7...10.6

Offer Marketing Illustration

Product benefits / Features

---

## 22 mm plastic pushbuttons and switches

Easy Harmony XA2



Easy installation  
and connection



Product  
robustness



Robust design for  
harsh environments



Ease and comfort of  
product selection



Wide  
availability



Groomed  
ergonomics



Offer Marketing Illustration

Product benefits / Features

---

## Technical Features

### Easy Harmony XA2



Offer Marketing Illustration

Product benefits / Features

---

**Features**  
Easy Harmony XA2

-  Cost effective plastic pushbuttons with metallic-look ring
-  Full function solution fit to customer needs
-  Modular design allows flexible and simple setup for complete products
-  Strong robustness and harsh environment protection
-  Wide availability throughout an extensive distribution network



Image of product / Alternate images

Alternative

---

