

Tehničke karakteristike proizvoda

Karakteristike

XALK178E

žuta upr. kutija - 1 crveni pečurkasti taster Ø40
otpuštanje zakretanjem 1NO+1NC



Osnovne informacije

Grupa proizvoda	Harmony XALK
Tip proizvoda ili komponente	Kompletna upravljačka stanica
Kratko ime uređaja	XALK
Namena proizvoda	Za XB5 Ø 22 mm upravljačko signalne elemente
Upotreba upravljačke stanice	Funkcija nužnog isključenja bez okidanja Funkcija nužnog isključenja
Boja osnova kućišta	Light grey (RAL 7035)
Boja poklopca	Yellow (RAL 1021)
Materijal	Polikarbonat
Glava uređaja	1 pečurkasta glava
Obeležavanje glave	Crveni neoznačen 1 NO + 1 NC
Reset	Otpuštanje zakretanjem
Sastav upravljačke stanice	1 pečurkasta glava Ø 40 mm, crvena 1 NO + 1 NC neoznačeno oznaka
Operacija kontakata	Sporo isključenje

Dopunske informacije

Kablovski uvod	1 knock-out for cable entry 0...14 mm 2 knock-outs for Pg 13 cable gland and ISO M20 0...12 mm
Masa proizvoda	0,194 kg
Otpornost na uređaj za pranje pod pritiskom	7000000 Pa at 55 °C, distance : 0.1 m
Pozitivno otvaranje	With conforming to EN/IEC 60947-5-1 appendix K
Put u radu	1.5 Mm (NC changing electrical state) 2,6 Mm (NO menja električno stanje) 4.3 mm (total travel)
Sila u radu	44 N NC + NO menjaju električno stanje
Mehanička trajnost	300000 ciklusa
Povezivanje - priključci	Screw clamp terminals, ≤ 2 x 1.5 mm² with cable end conforming to EN/IEC 60947-1 Vijčani priključni blokovi, ≥ 1 x 0.22 mm² bez kablovskog završetka u skladu sa EN/IEC 60947-1
Moment pritezanja	0.8...1.2 N.m conforming to EN/IEC 60947-1
Oblik glave zavrtnja	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver
Materijal kontakata	Legura srebra (Ag/Ni)
Zaštita od kratkog spoja	10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1
[i _{th}] dozvoljena termička struja u vazduhu	10 A conforming to EN/IEC 60947-5-1
[u _i] nazivni napon izolacije	600 V (stepen zaprljanosti 3) u skladu sa EN/IEC 60947-1
[u _{imp}] nazivni podnosivi impulsni napon	6 kV u skladu sa EN/IEC 60947-1
[i _e] nazivna radna struja	3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1

Električna trajnost	1000000 Cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C
Električna pouzdanost iec 60947-5-4	$\Lambda < 10\exp(-6)$ at 5 V, 1 mA conforming to EN/IEC 60947-5-4 $\Lambda < 10\exp(-8)$ at 17 V, 5 mA conforming to EN/IEC 60947-5-4

Okruženje

Tretman zaštite	TH
Temperatura okoline za skladištenje	-40...70 °C
Temperatura okoline za rad uređaja	-40...70 °C
Kategorija prenapona	Class II conforming to IEC 60536
Ip stepen zaštite	IP66 conforming to IEC 60529 IP67 IP69 IP69K
Nema stepen zaštite	NEMA 13 NEMA 4X
Ik stepen zaštite	IK03 conforming to EN 50102
Standardi	EN/IEC 60947-5-4 CSA C22.2 No 14 UL 508 EN/IEC 60947-5-5 EN/ISO 13850 EN/IEC 60947-5-1 JIS C 4520 IEC 60364-5-53 EN/IEC 60947-1 EN/IEC 60204-1
Otpornost na vibracije	5 gn (f= 12...500 Hz) u skladu sa IEC 60068-2-6
Otpornost na udare	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

Pakovanje

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	167 g
Pakovanje 1 visina	9,7 cm
Pakovanje 1 širina	7 cm
Pakovanje 1 dužina	7 cm
Pakovanje 2 težina	7,18 kg
Pakovanje 3 težina	67,644 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)  EU RoHS deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda

Profil cirkularnosti	 Informacije O Kraju Radnog Veka
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Ugovorna garancija	
Garancija	18 months