

Tehničke karakteristike proizvoda

Karakteristike

ZB2BC4C

Glava pečurkastog tastera, Easy Harmony XB2, 40mm, metalni, crvena, 22mm, sa povratkom



Osnovne informacije

Grupa proizvoda	Easy Harmony XB2
Tip proizvoda ili komponente	Glava za nesvetleći taster
Kratko ime uređaja	XB2
Materijal podnožja	Hromirani metal
Prečnik za montiranje	22,5 mm
Prodaja po nedeljivim količinama	1
Prezentacija uređaja	Osnovni element

Dopunske informacije

Kompatibilnost proizvoda	XB2..C
Lokacija za montiranje	Panel
Oblik glave signalne jedinice	Okrugla
Tip glave uređaja	Sa povratkom
Reset	Spring reset
Profil glave uređaja	Crvena pečurkasti taster Ø 40 mm, neoznačeno
Mehanička trajnost	3000000 ciklusa
Visina	40 mm
Širina	40 mm
Dubina	46 mm
Masa proizvoda	0,045 kg
Tip glave	Standardni
Boja kapica/glave ili sočiva	Crvena
Označavanje	Neoznačeno
Izolacija	Ne
Tip glave	Pečurkasti taster Ø 40 mm
Tip ručice	Sa povratkom

Okruženje

Tretman zaštite	TC/TH
Temperatura okoline za skladištenje	-40...70 °C
Temperatura okoline za rad uređaja	-25...70 °C
Standardi	EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-1 GB/T 14048.1 GB/T 14048.5
Sertifikacija proizvoda	CCC[RETURN]CE
Otpornost na vibracije	5 gn (f= 2...500 Hz) u skladu sa IEC 60068-2-6

Otpornost na udare	30 gn (trajanje = 18 milisekundi) za ubrzanje polovine sinusne periode u skladu sa IEC 60068-2-27 50 gn (trajanje = 11 milisekundi) za ubrzanje polovine sinusne periode u skladu sa IEC 60068-2-27
Ip stepen zaštite	IP65
Ik stepen zaštite	IK06


Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2,174 cm
Package 1 Width	3,999 cm
Package 1 Length	4,556 cm
Package 1 Weight	40 g
Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4,901 kg
Unit Type of Package 3	P06
Number of Units in Package 3	2000
Package 3 Height	90 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	103,2 kg

Održivost ponude


Status održive ponude	Green Premium proizvod
Propis REACH	 REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)  EU RoHS deklaracija
Bez žive	Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Informacije o RoHS izuzecima	 Da
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Nema potrebe za namenskim operacijama recikliranja

Dimensions



Mounting and Clearance

Panel cut-out



	Connection by Screw clamp terminals			
	a in mm	a in in.	b in mm	b in in.
•B2BA•C / •B2BL•C / •B2BP•C / •B2BS4•C / •B2BD•C / •B2BJ•C / •B2BG•C / •B2BW•C	40	1.57	30	1.18
•B2BC•C / •B2BS5•C / •B2BS8•C / •B2BT•C	40	1.57	40	1.57
•B2BR•C / •B2BS6•C	60	2.36	60	2.36

(1) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm₀^{+0.4} / 0.88 in.₀^{+0.016})