



Osnovne informacije

Grupa proizvoda	OsiSense XC
Ime serije	Standardni format
Tip proizvoda ili komponente	Glava graničnog prekidača
Kratko ime uređaja	ZCKD
Tip glave	Obrtna glava
Kompatibilnost proizvoda	XCKS XCKM XCKL
Pridružena ručica	ZCKY39 ZCKY33 ZCKY91 ZCKY43 ZCKY59 ZCKY54 ZCKY81 ZCKY31 ZCKY55 ZCKY41 ZCKY49 ZCKY34

Pridruženo telo	ZCKMD37H7 ZCKMD37H29 ZCKM1H29 ZCKL7H7 ZCKM1 ZCKL1 ZCKSD39H29 ZCKL8H7 ZCKSD37 ZCKM5H7 ZCKSD31H29 ZCKMD31H29 ZCKSD31 ZCKLD35H7 ZCKM6H29 ZCKLD31H7 ZCKMD37 ZCKLD39 ZCKS7 ZCKLD39H7 ZCKL1H7 ZCKM5 ZCKS404H29 ZCKMD39H29 ZCKS8 ZCKMD35 ZCKM9 ZCKS2 ZCKMD35H7 ZCKL7 ZCKM6 ZCKM8H7 ZCKL5 ZCKLD37H7 ZCKMD39H7 ZCKSD35H29 ZCKS7H29 ZCKS6H29 ZCKSD37H29 ZCKS1H29 ZCKL6 ZCKM9H29 ZCKM7 ZCKSD35 ZCKLD37 ZCKM7H29 ZCKS9H29 ZCKS9 ZCKMD31H7 ZCKS8H29 ZCKM6H7 ZCKM1H7 ZCKLD31 ZCKM8H29 ZCKS5 ZCKS1 ZCKL8 ZCKS2H29 ZCKL6H7 ZCKM7H7 ZCKL5H7 ZCKMD35H29 ZCKMD31 ZCKLD35 ZCKM8 ZCKMD39 ZCKS5H29 ZCKS6 ZCKM5H29 ZCKSD39
Kretanje glave	Obrtno
Tip glave uredaja	Bez poluge sa povratkom
Tip prilaza	Lateral approach, 1 or 2 programmable direction

Dopunske informacije

Aktiviranje prekidača	Sa leve strane i/ili desne U smeru kazaljke na satu i/ili u smeru suprotnom od kazaljke na satu
Pozitivno otvaranje	Bez Sa
Materijal glave	Plastika

Okruženje

Temperatura okoline za rad uređaja	-25...70 °C
Temperatura okoline za skladištenje	-40...70 °C
Karakteristike životne sredine	Standardna sredina

Pakovanje

Pakovanje 1 težina	0,074 kg
Pakovanje 1 visina	0,330 dm
Pakovanje 1 širina	0,630 dm
Pakovanje 1 dužina	0,750 dm

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS) EU RoHS deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	Da
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda

Ugovorna garancija

Garancija	18 meseci
-----------	-----------